

## 2800T

---

The 2800T brings you through-the-wall convenience and the latest advancements in ATM technology. Plus, the appealing and weatherized exterior is suitable for even the most high-end locales. This heavy-duty machine gives you the dependability and ease of maintenance with the added bonus of high-capacity note storage. You get the same high quality and proven reliability you expect from industry leader Hyosung.

## Features

---

### INNOVATIVE DESIGN

The 2800T offers a wide range of transactions and features a user-friendly interface with a large 12.1" display screen and tactile touch with function keys.

### CAPACITY

A significant advantage of the 2800T ATM is its high-capacity note storage able to accommodate up to three removable cassettes to make managing your cash easier.

### RELIABILITY

Ease of maintenance and simplified service routines provide maximum availability and increased uptime with minimal operational intervention.

### VISIBILITY

The built-in LED backlit sign makes this already attractive ATM even more visible. Add a video topper to stream advertising of your choice to attract more sales and customers.



## Standard Features

### Dimensions

- Height: (1828 mm)
- Width: (400 mm)
- Depth: (670 mm) for 3" wall
- Depth: (848 mm) for 10" wall
- Weight: (150 kg)

### Environmental

- Storage Temperature: 32°F - 104°F (0°C ~ 40°C)
- Humidity: 10–90%
- Operational Temperature: 41°F - 95°F (5°C ~ 35°C)
- Humidity: 25–85%

### SOFTWARE

- Microsoft® Windows® CE 6.0

### Card Reader

- EMV Dip type card reader
- IC Card Reader (optional)
- Anti-skimming (optional)
- ISO 1,2,3 Read-Magnetic Stripe

### Customer Interface

- 8" wide TFT LCD, 1024 x 768 resolution, brightness: 240cd/m3

### Media Technology

- 3 cassettes 2,000 notes each
- 40 notes/transaction
- Note by Note reject (200 bills max)

### Security

- UL291 business hour safe
- UL Level-1 option
- Dial lock (option), electronic lock (standard), Cencon lock (option)

### Communication

- TCP/IP. Dial-up

### Power Supply

- Input Voltage / Currency: 100W Free Voltage (90-264VAC), 90 – 132 Vac / 5.0A; 180 – 264 Vac / 2.5A
- Frequency: 47 – 63 Hz

### Input Type

- 8 tactile touch function keys
- PCI compliant EPP 8000M
- ADA compliant
- Touch F-key 4x2 NDC
- RKT (optional)

### Wall Kit

- 3" throat (standard)
- 10" throat (optional)

### Printers

- Thermal receipt printer
- Speed: 100mm/sec

### Additional Information

- Weatherized (water proof)
- Flicker
- Illuminated topper
- Audio jack
- EPP illumination
- Speaker
- Braille keypad
- Electronic journal
- Digital receipt
- Supports six languages; English, Spanish, French, Japanese, Chinese, Korean
- Enhanced Standard 1 (Hyosung Standard) DCC (Dynamic Currency Conversion)
- Heater (optional)

\*Subject to note quality and other variables

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.

Features and benefits are for U.S. configuration only. If located outside of the U.S., please contact sales.

