



HERCULES

Scale faster with the Hercules platform featuring built-in RMS.

Reduce failed transactions, increase ATM usage, and decrease tech dispatches. Known for its consistency and reliability (especially in fringe areas), the Hercules platform is referred to as the “gold standard” among ATM operators.

RMS Minus the Cost and Complexity

Level the playing field with Hercules RMS for your entire fleet - regardless of manufacturer - included with every Hercules and setup in minutes.

- Resolve transaction disputes
- View cash levels & forecasts
- Set & adjust bill counts
- View Terminal IDs
- Review e-journals
- View ATM errors
- View ATM status
- And more!



Purpose built for ATMs

Ideal for low data usage applications such as ATMs, vending machines, and wireless laundry facilities, the Hercules features tons of standard features.

- 5 Year warranty
- 24/7/365 Support & Network monitoring
- Unlimited transactions
- Multiple wireless carrier options
- Failover to wireless capability
- Customer portal
- Solid metal case
- EMV and DCC Capable

dplwireless.com/hercules



HERCULES

Specifications

WARRANTY	30-day return policy and a 5-year warranty with immediate RMA replacement. 2-year warranty on battery.
FREQUENCY BANDS	Verizon: LTE - B4/B13 AT&T/Bell/Rogers: LTE - B2/B4/B5/B12, HSPA - B2/B4/B5
ETHERNET PORT INTERFACE PORT	Supports 10/100T speeds and straight or crossover cables Custom port for Restart accessory
PROTOCOLS SUPPORTED	AES-256, DH-1024, MAC, DHCP (client and server), NAT, IP filtering, HDLC/PPP/PAP/ LCP/PCP, TCP, UDP, ICMP, DNS, Ethernet, VISA-2
NETWORK SERVICES	CAT4 Data over 5G/LTE network . ATM510 LTE has ability to fall back to 3G/HSPA (carrier dep.)
POWER SUPPLY OUTPUT	12VDC, 2A, Center Positive, 5.5mm x 2.1mm
POWER SUPPLY INPUT	100-240VAC, 50-60 Hz, 1.0 A Max
DIMENSIONS (H W D)	3.8 x 12.2 x 14.5 cm (1.5 x 4.8 x 5.7 inches)
WEIGHT	0.43kg (0.95lb)
PACKAGED DIMENSIONS (H W D)	5.715 x 27.94 x 15.24 cm (2.25 x 11 x 6 inches)
PACKAGED WEIGHT	0.976kg (2.15lb)
OPERATING TEMP	-10 to 45 °C (14 to 113 °F)
REGULATORY	FCC Part 15, Subpart B, ISED Canada ICES-003, Issue 7 - ITE
NETWORK OPERATOR STANDARDS	PTCRB Certification Test Standards: ETSI TS 102.230 V 14.1.0 & TS 36.124 V15.20,
NETWORK OPERATOR CERTIFICATIONS	Verizon, AT&T, Rogers Communications



dplwireless.com/hercules